



CATALOG NUMBER	NOM DIA	D-1	D-2	L-1 +.002/-.000	T-1	PRICE
DSL-0	1/4"	0.2506/0.2508	0.2180	0.3750	#8-36 NF	\$94.00
DSL-1	3/8"	0.3756/0.3758	0.3270	0.5630	1/4-28 NF	\$74.00
DSL-2	1/2"	0.5006/0.5008	0.4350	0.7500	5/16-24 NF	\$83.00
DSL-13	3/4"	0.7506/0.7509	0.6500	0.7500	N/A	\$106.00
DSL-14	1"	1.0006/1.0009	0.8660	1.0000	N/A	\$121.00

### Same great advantages as the DWD Original series:

- Corrosion resistant 17-4PH stainless steel
- Bolt-in mount or press-fit styles available
- Superior air flow via access holes
- Low cost
- Stainless steel screws available upon request
- Complete family of components

### STAINLESS STEEL SCREWS

Size	#8-36	1/4-28	5/16-24
Length			
0.38 lg	N/A	N/A	N/A
0.50 lg	N/A	X	X
0.75 lg	X	X	X
1.00 lg	N/A	X	X
1.25 lg	N/A	X	X
1.50 lg	N/A	X	X
1.75 lg	N/A	X	X
2.00 lg	N/A	X	X
2.25 lg	N/A	X	N/A
2.50 lg	N/A	X	X
3.00 lg	N/A	X	X

(Sold Separately)

### PLUS! These new “SL” features:

- Guide sleeve for axial alignment
- Sleeve reduces wear on cross pin
- Positive stop to reduce spring fatigue
- High pressure spring for tighter seal and resistance to vacuum
- Spring rated for high temperature environments such as compression molds & rotomolds
- Life tested at 1,000,000 cycles